

## DECLARATION OF PERFORMANCE

Nro. 097-FF-2019-01-01

1. **Unique identification code of the product-type:** Tulppa wetroom board -80mm
2. **Allowing identification of the construction product:** Check label.
3. **Intended uses of the construction product:** The boards are used for waterproofing wet rooms, as well as various structures in wet areas as building board. Product applications are specified in the web site [www.tulppa.fi](http://www.tulppa.fi) .
4. **Name, registered trade name and contact address of the manufacturer:**

Finnfoam Oy (0689386-6)

Satamakatu 5

24100 Salo, Finland

Tel. +358 2 777 300

Fax: +358 2 777 3020

Email: [finnfoam@finnfoam.fi](mailto:finnfoam@finnfoam.fi)

5. **System of attestation of conformity:** AVCP 2+
6. **Declaration of performance concerning a construction product for which a European Technical Assessment has been issued:**

Eurofins Expert Services (NB.0809) issued European Technical Assessment ETA-13/0820, on the basis of Etag 022 part 3, after performed product plant and internal factory production control initial inspection under system 2+ and issued factory production control certificate of conformity no.0809-CPR-1187.

**Tulppa**<sup>®</sup>  
MÄRKÄTILALEVYT

9. Declared performance:

Essential characteristics	Performance	European Technical Assessment
Reaction to fire	NPD	Etag 022-3
Release of dangerous substances	No releases/M1	
Moisture resistance	Tulppa 80mm: $19 \times 10^{-12} \text{ Kg}/(\text{m}^2\text{s Pa})$	
Water tightness (board)	Water tight	
Crack bridging ability	NPD	
Bond strength	<b>ARDEX X 77:</b> Category 1 $\geq 0,2\text{MPa}$ <b>Casco Multifix Superflex:</b> Category 1 $\geq 0,2 \text{ MPa}$ <b>Schönox Q 12:</b> Category 1 $\geq 0,2 \text{ MPa}$ <b>Kiilto superfix DF:</b> Category 1 $\geq 0,2 \text{ MPa}$ <b>Kiilto highflex S2 DF:</b> Category 1 $\geq 0,2 \text{ MPa}$ <b>Weber rex fix:</b> Category 1 $\geq 0,2 \text{ MPa}$ <b>Fescon VSL:</b> Category 1 $\geq 0,2 \text{ MPa}$	
Joint bridging ability <b>Ardex CA 20 P</b> <b>Sikaflex AT-connection</b> <b>Casco Aquaseal</b>	Category 2: Water tight	
Watertightness around penetrations <b>Ardex 8+9</b> <b>Ardex S 1-K</b> <b>Casco Aquastop</b> <b>Weber.Vetonit WP</b>	Category 2: Water tight	
Thermal conductivity $\lambda_D$	0,037 W/mK	
Resistance to temperature	<b>Bond strength:</b> <b>ARDEX X 77:</b> Category 1 $\geq 0,2\text{MPa}$ <b>Casco Multifix Superflex:</b> Category 1 $\geq 0,2 \text{ MPa}$ <b>Schönox Q 12:</b>	

	<p>Category 1 <math>\geq 0,2</math> MPa  <b>Kiilto Superfix DF:</b>          Category 1 <math>\geq 0,2</math> MPa  <b>Kiilto Highflex S2 DF:</b>          Category 1 <math>\geq 0,2</math> MPa  <b>Weber rex fix:</b>          Category 1 <math>\geq 0,2</math> MPa  <b>Fescon VSL:</b>          Category 1 <math>\geq 0,2</math> MPa  <b>Bending strength:</b>          Change after heat ageing <math>\leq 20</math> %</p>	
Resistance to water	Pass	
Resistance to water	<p><b>Bond strength:</b>  <b>ARDEX X 77:</b>          Category 1 <math>\geq 0,2</math>MPa  <b>Casco Multifix Superflex:</b>          Category 1 <math>\geq 0,2</math> MPa  <b>Schönox Q 12:</b>          Category 1 <math>\geq 0,2</math> MPa  <b>Kiilto Superfix DF:</b>          Category 1 <math>\geq 0,2</math> MPa  <b>Kiilto Highflex S2 DF:</b>          Category 1 <math>\geq 0,2</math> MPa  <b>Weber rex fix:</b>          Category 1 <math>\geq 0,2</math> MPa  <b>Fescon VSL:</b>          Category 1 <math>\geq 0,2</math> MPa</p>	Etag 022-3
Resistance to alkalinity	<p><b>Tulppa –board</b>          Category 2 <math>\geq 0,2</math> MPa</p>	
Repairability	Repairable	
Thickness	80 mm	

Safety data sheet: [www.tulppa.fi/kayttoturvallisuustiedote](http://www.tulppa.fi/kayttoturvallisuustiedote)

Signed for and on behalf of the manufacturer by:

Henri Nieminen, CEO

Salo 1.1.2019

# SUORITUSTASOILMOITUS



(Signature)

**Tulppa**<sup>®</sup>  
MÄRKÄTILALEVY